



MODEL: TM-150 (PLASTIC CUP MACHINE)



TM-150 Machine Features

NO	DESCRIPTION	BRAND
1	MOULD FIXING AREA – 900 X 400 mm	-
2	FORMING AREA – 700 X 350 mm	-
3	MAX. PRODUCTION LENGHT 150 mm	-
4	MAIN MOTOR 7,5KW AC MOTOR (WITH EATON DRIVER / GERMANY)	YILMAZ – TURKEY
5	CHAIN MOVEMENT MOTOR – 3KW SERVO MOTOR	KHUNKE – GERMANY
6	UNWINDING MOTOR 0,75KW AC MOTOR	YILMAZ – TURKEY
7	REWINDER MOTOR – 0,75KW AC MOTOR	YILMAZ – TURKEY
8	12 INCH TOUCH SCREEN – MOVİBLE CONTROL PANEL	KHUNKE – GERMANY
9	INFRANED HEATERS / 30 HEATER ZONE CONTROL	ELSTEIN – GERMANY
10	AUTOMATIC LUBRICATION	LUBRIMAC - ITALY
11	AUTOMATIC LIFTING SYSTEM FOR ROLL	FESTO – GERMANY
12	ELECTRICAL EQUIPMENT	KHUNKE – GERMANY
13	PNEUMATIC EQUIPMENT	FESTO – GERMANY
14	TOTAL POWER CONSUMPTION 45 KW (RUNNING TIME)	-
15	TOTAL AIR CONSUMPTION 3 m3 PER. / MIN.	-
16	MACHINE MAX. SPEED WITH LOAD 35 CYCLE / MIN.	-
17	MACHINE CAN BE WORK P.P-P.S-PET MATERIAL	-
18	SHEET TENSION SYSTEM	-
19	HEIGHT: 3000mm – WIDTH: 2100mm – LENGHT: 6500mm WEIGHT: 4500kg.	-
20	INCLUDING PRE-HEATER TO MACHINE	-

PRODUCTIONS

